

- CONSTRUCTION**
- 4 jack rings for comfortable transportation
  - Forklift pockets for transport
  - Protective corners offer additional collision protection and stability
  - Best-Point-Technology (joining process, the protective zinc coating is not damaged)

- MATERIAL**
- Galvanized sheet steel S220 GD Z; 1.0241 and S250 GD Z; 1.0242
  - Surface: MB, hot-dip galvanized
  - Trapezoidal sheet thickness: 0.8mm
  - Profile thickness: 1.5mm or 2mm

- FLOOR**
- OSB/3 panel for use in structural applications in humid areas in accordance with EN 300
  - Panel thickness: 18mm
  - Load bearing capacity: 500kg/m<sup>2</sup> (permissible area load)
  - Fully PMDI (formaldehyde free) glued, low-emission (E1)
  - Guaranteed pest free (IPPC standard)
  - European building material classification according to EN 13501-1: D - s2, d0

- CRANE HANDLING**
- Can be lifted by crane when empty

**SIZE/WEIGHT**

BPH+	
Width external/internal (mm)	2100/1975
Length external/internal (mm)	2100/975
Height external/internal (mm)	2080/1935
Weight (incl. accessories) (kg)	280

- DOORS**
- SZ (in front face, double door), 1750 x 1890mm (clearance dimensions: 1758 x 1855mm)
  - Entrance height: approx. 105mm
  - With mortise lock (according to DIN 18251-1) and profile cylinder (PZ 25/25), including 3 keys
  - Short plate and door handle pair in aluminium
  - A door catch prevents the door from slamming

- DELIVERY**
- Assembled delivery

- ACCESSORIES ONLY FOR THE BPH**
- Drawing board (K 101 SM coated white) incl. shelf, two shelf supports and two shelf rackets (galvanized sheet steel)
  - Drawing shelf for 6 drawings (galvanized sheet steel)
  - Light panel (PVC trapezoid light panel, transparent, fire protection class according to DIN 4102-1: B1, European building material classification according to EN 13501-1: B - s1, d0)