

- CONSTRUCTION**
- 4 jack rings for comfortable transportation
 - Metal runners for fork-lift transport and ground ventilation
 - Protective corners offer additional collision protection and stability
 - Best-Point-Technology (joining process, the protective zinc coating is not damaged)

- MATERIAL**
- Galvanized sheet steel S220 GD Z; 1.0241 and S250 GD Z; 1.0242
 - Surface: MB, hot-dip galvanized
 - Trapezoidal sheet thickness: 0.8mm
 - Profile thickness: 1.5mm or 2mm

- FLOOR**
- OSB/3 panel for use in structural applications in humid areas in accordance with EN 300
 - Panel thickness: 18mm
 - Load bearing capacity: 500kg/m² (permissible area load)
 - Fully PMDI (formaldehyde free) glued, low-emission (E1)
 - Guaranteed pest free (IPPC standard)
 - European building material classification according to EN 13501-1: D - s2, d0

- SAFETY**
- GS mark from TÜV North

- CRANE HANDLING**
- MB1+: 300kg permissible total weight
 - MB2+: 600kg permissible total weight

- SNOW LOAD**
- 210kg/m²

- WIND LOAD**
- Wind load determination in accordance with DIN EN 1991-1-4

SIZE/WEIGHT

MB		1+	2+
Width external/internal	(mm)	1100/975	2100/1975
Length external/internal	(mm)	700/575	700/575
Height external/internal	(mm)	1600/1435	1600/1435
Height with castors external/internal	(mm)	1795/1435	1795/1435
Weight	(kg)	100	160

- DOORS**
- MB1: SE (in front face, single door), 750 x 1390mm (clearance dimensions: 758 x 1355mm)
 - MB2: SZ (in front face, double door), 1750 x 1390mm (clearance dimensions: 1758 x 1355mm)
 - With mortise lock (according to DIN 18251-1) and profile cylinder (PZ 25/25), including 3 keys
 - Short plate and door handle pair in aluminium

- DELIVERY**
- Assembled delivery

- ACCESSORIES ONLY FOR THE MB+**
- Swivel and fixed castors (Heavy duty wheel with elastic solid rubber tyres and aluminium wheel body, load: 300kg)