

## Technical Description

# MATERIAL CONTAINER MCL+

**CONSTRUCTION**

- Simple assembly in a very short time
- Best-Point-Technology (joining process, the protective zinc coating is not damaged)

**MATERIAL**

- Galvanized sheet steel S220 GD Z; 1.0241 and S250 GD Z; 1.0242
- Surface: MB, hot-dip galvanized
- Trapezoidal sheet thickness: 0.8mm
- Profile thickness: 1.5mm or 2mm

**FLOOR**

- OSB-Panel thickness: 18mm
- Squared timber: 80 x 80mm
- Load bearing capacity: 300kg/m<sup>2</sup> (permissible area load)

**SNOW LOAD**

- 210kg/m<sup>2</sup>

**SIZE/WEIGHT**

MCL+	2x2	3x2	4x2
Width external/internal (mm)	2100/1975	2100/1975	2100/1975
Length external/internal (mm)	2100/1975	3100/2975	4100/3975
Height external/internal (mm)	2180/1930	2180/1930	2180/1930
Weight (kg)	315	415	500

**DOORS**

- SE (in front face, single door), 1150 x 1890mm (clearance dimensions: 1158 x 1855mm)
- LE (in side wall, single door), 1150 x 1890mm (clearance dimensions: 1158 x 1855mm)
- Entrance height: approx. 105mm
- With mortise lock (according to DIN 18251-1) and profile cylinder (PZ 25/25), including 3 keys
- Short plate and door handle pair in aluminium

**DELIVERY**

- Flat-packed