



**CONSTRUCTION**

- Simple assembly in a very short time
- Metal runners for ground ventilation
- Protective corners offer additional collision protection and stability
- Best-Point-Technology (joining process, the protective zinc coating is not damaged)

**MATERIAL**

- Galvanized sheet steel S220 GD Z; 1.0241 and S250 GD Z; 1.0242
- Surface: MB, hot-dip galvanized
- Trapezoidal sheet thickness: 0.8mm
- Profile thickness: 1.5mm or 2mm

**FLOOR**

- OSB/3 panel for use in structural applications in humid areas in accordance with EN 300
- Panel thickness: 18mm
- Load bearing capacity: 500kg/m<sup>2</sup> (permissible area load)
- Fully PMDI (formaldehyde free) glued, low-emission (E1)
- Guaranteed pest free (IPPC standard)
- European building material classification according to EN 13501-1: D - s2, d0

**SIZE/WEIGHT**

SCC2400+ side to side	3x4	3x6	4x4	4x6	5x4	5x6
Width external/internal (mm)	4200/4075	6300/6175	4200/4075	6300/6175	4330/4205	6560/6435
Length external/internal (mm)	3100/2975	3100/2975	4100/3975	4100/3975	5100/4975	5100/4975
Height external/internal (mm)	2445/2280	2445/2280	2445/2280	2445/2280	2660/2280	2660/2280
Height lower edge gutter (mm)	2120	2120	2050	2050	2220	2220
Weight (kg)	770	1085	960	1360	1190	1715

**DOORS**

- LE (in side wall, single door), 1150 x 2235mm (clearance dimensions: 1158 x 2200mm)
- LZ (in side wall, double door), 1750 x 2235mm (clearance dimensions: 1758 x 2200mm)
- Entrance height: approx. 120mm
- With mortise lock (according to DIN 18251-1) and profile cylinder (PZ 25/25), including 3 keys
- Short plate and door handle pair in aluminium

**DELIVERY**

- Flat-packed delivery

**ASSEMBLY TIMES**

SCC2400+ side to side	3x4	3x6	4x4	4x6	5x4	5x6
Assembly time (h)	3,5	4,5	3,5	4,5	4,5	5,5
Number of people	2	2	3	3	4	4

- The table is intended as a guide only
- A forklift/crane is recommended for assembly