



CONSTRUCTION

- Simple assembly in a very short time
- Metal runners for ground ventilation
- Protective corners offer additional collision protection and stability
- Best-Point-Technology (joining process, the protective zinc coating is not damaged)

MATERIAL

- Galvanized sheet steel S220 GD Z; 1.0241 and S250 GD Z; 1.0242
- Surface: MB, hot-dip galvanized
- Trapezoidal sheet thickness: 0.8mm
- Profile thickness: 1.5mm or 2mm

FLOOR

- OSB/3 panel for use in structural applications in humid areas in accordance with EN 300
- Panel thickness: 18mm
- Load bearing capacity: 500kg/m² (permissible area load)
- Fully PMDI (formaldehyde free) glued, low-emission (E1)
- Guaranteed pest free (IPPC standard)
- European building material classification according to EN 13501-1: D - s2, d0

SIZE/WEIGHT

SCC2100+ end to end	6x2	7x2	7x2	9x2	10x2	11x2	12x2
Width external/internal (mm)	2100/1975	2100/1975	2100/1975	2100/1975	2100/1975	2100/1975	2100/1975
Length external/internal (mm)	6200/6075	7200/7075	8200/8075	9200/9075	10200/10075	11200/10075	12200/12075
Height external/internal (mm)	2100/1935	2100/1935	2100/1935	2100/1935	2100/1935	2100/1935	2100/1935
Height lower edge gutter (mm)	1875	1875	1875	1875	1875	1875	1875
Weight (kg)	750	855	965	1050	1135	1245	1350

DOORS

- SZ (in front face, double door, narrow), 1750 x 1890mm (clearance dimensions: 1758 x 1855mm)
- Entrance height: approx. 120mm
- With mortise lock (according to DIN 18251-1) and profile cylinder (PZ 25/25), including 3 keys
- Short plate and door handle pair in aluminium

DELIVERY

- Flat-packed delivery

ASSEMBLY TIMES

SCC2100+ end to end	6x2	7x2	7x2	9x2	10x2	11x2	12x2
Assembly time (h)	3	3	3	3	3	4	4
Number of people	2	3	3	4	4	4	4

- The table is intended as a guide only