

- CONSTRUCTION**
- Fully galvanized, welded and painted steel frame construction
 - Forklift pockets for transport
 - Insulation by means of high thermal insulating PUR sandwich panels, encased in galvanized and painted covering shells G 250 GD - EN 10346

- MATERIAL**
- Galvanized sheet steel, welded and painted in RAL 9002
 - 40mm sandwich panels, galvanized and painted in RAL 9002

- FLOOR**
- 18mm wooden floor
 - PVC flooring
 - Stainless steel access threshold
 - Load capacity: 200kg/m² (permissible area load)

- CRANE HANDLING**
- Can be lifted by crane when empty

- SNOW LOAD**
- 1.25kN/m²

- WIND LOAD**
- 0.7kN/m²

SIZE/WEIGHT

| TS+ | 3x2 | 4x2 | 6x2 |
|-------------------------------|-----------|-----------|-----------|
| Width external/internal (mm) | 2420/2250 | 2420/2250 | 2420/2250 |
| Length external/internal (mm) | 3090/2920 | 4090/3920 | 6090/5920 |
| Height external/internal (mm) | 2480/2200 | 2480/2200 | 2480/2200 |
| Weight (kg) | 690 | 810 | 1080 |

- DOORS**
- Insulated aluminium door with high quality seal
 - SE (in front face, 1 leaf), 1050 x 2200mm (clearance dimensions: 900 x 2100mm)
 - SZ (in front face, 2 leaf), 2050 x 2200mm (clearance dimensions: 1900 x 2100mm)
 - Entrance height: approx. 180mm
 - With mortise lock and profile cylinder, including 3 keys
 - Can be locked from the outside and inside

- INSULATION WALLS AND ROOF**
- Polyurethane (PUR) thermal insulation, free from CFCs and HCFCs, density 40kg/m³
 - Thickness: 40mm
 - European building material classification according to EN 13501-1: 2009
 - Thermal insulation
 - Roof elements U value 0.52W/(m²K) (DIN EN 14509), K value 0.55W/(m²K) (EN ISO 6946)
 - Wall elements U value 0.58W/(m²K) (DIN EN 14509), K value 0.55W/(m²K) (EN ISO 6946)
 - Insulating panel cartridges with galvanized sheet steel on both sides coated with RAL 9002

- DELIVERY**
- Assembled delivery

- ACCESSORIES ONLY FOR THE TS+**
- Insulated floor (with mineral wool filling)
 - Double leaf door 1800 x 2200mm
 - Electrical package (10W LED light with switch, 16A Schuko plug, fuse box, outdoor connection and earth cable)
 - Wall convector DX 420, Size: 575 x 350 x 124mm, Weight: 4.1kg, Colour: white, Power supply: 2.0kW, Protection type: IP20, Variable temperature control: + 5 to + 35°C, Overheat protection and automatic frost protection
 - White aluminium sliding window (Size: 760 x 1020mm)