

## Technical Description

# TOOL SECURITY BOX WSB+

- CONSTRUCTION**
- 4 jack rings for comfortable transportation
  - Metal runners for fork-lift transport and ground ventilation
  - 4 handles for manual transport
  - Gas struts prevent slamming of the lid
  - Protective corners offer additional collision protection and stability
  - Best-Point-Technology (joining process, the protective zinc coating is not damaged)
- MATERIAL**
- Galvanized sheet steel S220 GD Z; 1.0241 and S250 GD Z; 1.0242
  - Surface: MB, hot-dip galvanized
  - Trapezoidal sheet thickness: 0.8mm
  - Profile thickness: 1.5mm or 2mm
- FLOOR**
- OSB/3 panel for use in structural applications in humid areas in accordance with EN 300
  - Panel thickness: 18mm
  - Load bearing capacity: 500kg/m<sup>2</sup> (permissible area load)
  - Fully PMDI (formaldehyde free) glued, low-emission (E1)
  - Guaranteed pest free (IPPC standard)
  - European building material classification according to EN 13501-1: D - s2, d0
- CRANE HANDLING**
- 250kg permissible total weight
- SIZE/WEIGHT**
- | WSB+                          |           |
|-------------------------------|-----------|
| Width external/internal (mm)  | 1900/1770 |
| Length external/internal (mm) | 700/570   |
| Height external/internal (mm) | 875/750   |
| Weight (kg)                   | 105       |
- DELIVERY**
- Assembled delivery
- ACCESSORIES ONLY FOR THE WSB**
- 2 discus locks (simultaneous locking) with 2 keys each